

MPB750M

POWER SUPPLY

SPECIFICATIONS

Power	750W
AC input	200-240V 47-63Hz
PFC	Active
Efficiency	90%
Noise	14dB
Form Factor	ATX
Fan	140mm
Rail	Single 12V
Certificate	ATX12V, CE, ROHS
Protections	OPP, OVP, UVP, SCP, OCP
Cable type	Full modular
Cables	1x20 + 4 pin, 1x12V 4 + 4 pin, 5xSATA, 3xMOLEX, 2x6+2 pin PCI-E
Dimensions	150x160x85mm / 1.6Kg
Extra	AI-RPM fan control and extra long flat cables

750W ATX fully modular power supply with 80PLUS BRONZE 230V EU certification and +90% efficiency

6 years warranty and SMD technology with A-Grade components

Single 12V rail and AI-RPM for an optimized temperature control

Flat cables



AC Input	200-240Vac	5A	47-63Hz		
DC Output Voltage	+3.3V	+5V	+12V	-12V	+5Vsb
Max. Output Current	25A	25A	62A	0.5A	3A
Combined Power	130W	744W	6W	15W	
Total Power	750W				



LOGISTICS

REFERENCE **MPB750M**

UNITS/BOX **10**

EAN **8435693103172**

PACKAGING **206x136x258mm**